

SUBAL CD3

for Canon EOS 1D/1Ds Mark III



Controls/Functions:

Power On - Off, Shutter Release, Zoom (manual focus), Front and Rear Main Dial, Lense Release, AF - ON, Cursor.

Push Buttons for:

Mode, AF - Drive, Metering Selector - Flash Compensation, Light, ISO, Exposure Compensation, Menu, Info, Playback, Delete, Func., Protect, Set, Exposure Storage, AF-Area Selector, FEL.

Technical Data:

Seawater resistant aluminium alloy, machined from block, extreme surface hardening and corrosion resistance through HardCoating. All parts manufactured from anodized and hard coated aluminium, acid proof stainless steel or high quality plastics. Seals are seamless precision O-rings.

O-rings in hard coated glands.

SUBAL QuickLock latching system.

With the **SUBAL CD3** SUBAL offers an aluminium housing for the digital SLR-camera Canon EOS 1D/1Ds Mark III. The camera is mounted on a saddle for precise positioning inside the housing. Ergonomic placement of all important controls provides convenient and comfortable handling of the camera functions.

A 4 mm main-O-ring and the SUBAL QuickLock latching system make it virtually impossible to close the lid if the O-ring is not lying correctly in its groove. Maximum security is assured. Threaded holes on the base and in the top shoe allows mounting of trays, aiming lights or other accessories. Generous shading of the LCD-monitor provides a bright and clear image.

The housing incorporates an excellent viewfinder optic for full frame viewing. Optionally the housing can be assembled with the new magnifying **Viewfinder Optic GS 180**.

As with all our products choice of materials, machining, surface protection and finish conform with SUBAL's well known standards of reliability and workmanship.

All SUBAL ports with bayonet mount are fitting this housing.



Configuration:

- **W x H x D** Approx. 255 x 235 x 155 mm (w/o port and handles)
- **Weight** Approx. 2,7 kg (w/o port and accessories)
- **Buoyancy** All but neutral (depended on used port and accessories)
- **2 Flash connectors** Optionally Nikonos V, IKELITE or subtronic S6 sockets. TTL mode available ONLY with S6 socket and original Canon flush gun!
- **Strobe arm mounts** Two 25 mm T-plates, TLC- or Ultralight base optional
- **Max. Depth rating** 70 m (210 ft)

